



Outdoor spotlight for ground installation

Material: luminaire in anodized anticorrosive turned aluminium /  
Anti-glare shield in anodized anticorrosive extruded aluminium

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN  
61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN  
61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization

On request versions (additional code):

**MT7** 7 m cable length

Dimensions	<b>Ø 49 x L 144 mm</b>
Light source	<b>LED</b>
Wattage	<b>4 W</b>
Power supply	<b>24 Vdc</b>
Light source output	<b>470 lm</b>
System output	<b>355 lm</b>
System efficiency	<b>89 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>E (3000K), E (4000K), F (2700K)</b>
LED lifetime	<b>L80 B10 86.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class III</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Conformity	<b>CE UK CA</b>

## CODE OPTIONS

### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

### OPTIC

**standard** 30°  
optional optics  
**10** 10°  
**54** 54°

ACCESSORIES

