

Outdoor spotlight for ground installation

Material: luminaire in anodized anticorrosive turned aluminium /
Anti-glare shield in anodized anticorrosive extruded aluminium

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN
61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN
61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable

Finish: anodization

On request versions (additional code):

MT7 7 m cable length

| | |
|--|--|
| Dimensions | Ø 49 x L 144 mm |
| Light source | LED |
| Wattage | 4 W |
| Power supply | 24 Vdc |
| Light source output | 470 lm |
| System output | 355 lm |
| System efficiency | 89 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E (3000K), E (4000K), F (2700K) |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class III |
| IP rating | IP 65/67 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 30°
optional optics
10 10°
54 54°

DART SPOT Ø 49 LED 4W – 24V

1619

ACCESSORIES

ACCESSORIES
24V DRIVER – 24W



1924

ACCESSORIES
24V DRIVER – 60W




1925

DART SPOT
STRAP



1601

DART SPOT
SPIKE



1600

ACCESSORIES
PWM DRIVER



1953