

Garden stem complete with luminaire

Material: luminaire in anodized anticorrosive turned aluminium /  
Anti-glare shield and stem in anodized anticorrosive extruded  
aluminium / Die-cast aluminium base

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN  
61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN  
61347-2-13 Standard, to be ordered separately

Light source: LED module

Supplied with 1,5 m cable (from the luminaire)

Finish: anodization

On request versions (additional code):

**MT7** 7 m cable length

Dimensions	<b>Ø 50 x L 125 x H 650 mm</b>
Light source	<b>LED</b>
Wattage	<b>2 W</b>
Power supply	<b>24 Vdc</b>
System output	<b>126 lm</b>
System efficiency	<b>63 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>F</b>
Electrical insulation class	<b>Class III</b>
IP rating	<b>IP 65/67</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>0.36 kg</b>
Conformity	<b>CE UK CA</b>

### CODE OPTIONS

#### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

#### OPTIC

**standard** 27°

optional optics

**11** 11°  
**42** 42°

ACCESSORIES

ACCESSORIES  
24V DRIVER – 24W



1924

ACCESSORIES  
24V DRIVER – 60W




1925

ACCESSORIES  
PWM DRIVER



1953

DART STEM  
SPIKE



1670