# DART STEM Ø 49 H 500 LED 4W

## 1681






Garden stem complete with luminaire

Material: luminaire in anodized anticorodal turned aluminium / Anti-glare shield and stem in anodized anticorodal extruded aluminum / Die-cast aluminium base

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Supplied with 1,5 m cable (from the luminaire)

Finish: anodization

On request versions (additional code):
MT7 7 m cable length

| | |
|---|---|
| Dimensions | Ø 70 x L 180 x H 500 mm |
| Light source | LED |
| Wattage | 4 W |
| Power supply | 220-240 V \| 50/60 Hz |
| Light source output | 470 lm |
| System output | 355 lm |
| System efficiency | 89 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | E (3000K), E (4000K), F (2700K) |
| LED lifetime | L80 B10 86.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class I |
| IP rating | IP 65/67 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Conformity | CE UK CA |

## CODE OPTIONS

### FINISH

| | |
|---|---|
| **OS** | NATURAL ANODIZATION |
| **ON** | BLACK ANODIZATION |

### COLOUR TEMP.

| | |
|---|---|
| **27K** | 2700K |
| **3K** | 3000K |
| **4K** | 4000K |

### OPTIC

| | |
|---|---|
| **standard** | 30° |

optional optics

| | |
|---|---|
| **10** | 10° |
| **54** | 54° |

# DART STEM Ø 49 H 500 LED 4W

## 1681

## ACCESSORIES

ACCESSORIES
SPIKE



4696

ACCESSORIES
ANCHOR PLATE



4697

ACCESSORIES
IN-GROUND BOX



4698



**Goccia Illuminazione srl**
via E.Fermi 59/65 - 25020 Poncarale (BS) Italy
+39 030 2640761 - info@www.goccia.it