

Garden stem complete with luminaire

Material: luminaire in anodized anticorodal turned aluminium / Anti-glare shield and stem in anodized anticorodal extruded aluminium / Die-cast aluminium base

Diffuser: ultra-white transparent tempered glass

Built-in driver

Light source: LED unit

Supplied with 1,5 m cable (from the luminaire)

Finish: anodization

On request versions (additional code):  
MT7 7 m cable length

Dimensions	Ø 70 x L 180 x H 500 mm
Light source	LED
Wattage	4 W
Power supply	220-240 V   50/60 Hz
Light source output	470 lm
System output	355 lm
System efficiency	89 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION

### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K


### OPTIC

**standard** 30°  
optional optics  
**10** 10°  
**54** 54°




ACCESSORIES

ACCESSORIES  
SPIKE




4696

ACCESSORIES  
ANCHOR PLATE



4697

ACCESSORIES  
IN-GROUND BOX



4698