

Garden stem complete with luminaire

Material: luminaire in anodized anticorrosive turned aluminium / Anti-glare shield and stem in anodized anticorrosive extruded aluminium / Die-cast aluminium base

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable (from the luminaire)

Finish: anodization

On request versions (additional code):

**MT7** 7 m cable length

|  |  |
|--|--|
| Dimensions                               | <b>Ø 70 x L 180 x H 500 mm</b>         |
| Light source                             | <b>LED</b>                             |
| Wattage                                  | <b>4 W</b>                             |
| Power supply                             | <b>24 Vdc</b>                          |
| Light source output                      | <b>470 lm</b>                          |
| System output                            | <b>355 lm</b>                          |
| System efficiency                        | <b>89 lm/W</b>                         |
| Color Rendering Index – CRI              | <b>80</b>                              |
| LED energy class                         | <b>E (3000K), E (4000K), F (2700K)</b> |
| LED lifetime                             | <b>L80 B10 86.000 h</b>                |
| Standard Deviation Color Matching (SDCM) | <b>MacAdam step 3</b>                  |
| Electrical insulation class              | <b>Class III</b>                       |
| IP rating                                | <b>IP 65/67</b>                        |
| Impact resistance rating                 | <b>IK 08 (5 Joules)</b>                |
| Norms                                    | <b>EN 60598-1 +2-1</b>                 |
| Conformity                               | <b>CE UK CA</b>                        |

**CODE OPTIONS**

**FINISH**

**OS** NATURAL ANODIZATION  
**ON** BLACK ANODIZATION

**COLOUR TEMP.**


**27K** 2700K  
**3K** 3000K  
**4K** 4000K

**OPTIC**

**standard** 30°  
optional optics  
**10** 10°  
**54** 54°


ACCESSORIES

ACCESSORIES  
SPIKE




**4696**

ACCESSORIES  
ANCHOR PLATE



**4697**

ACCESSORIES  
IN-GROUND BOX



**4698**

ACCESSORIES  
24V DRIVER – 24W



**1924**

ACCESSORIES  
24V DRIVER – 60W



**1925**

ACCESSORIES  
PWM DRIVER



**1953**