

Garden stem complete with luminaire

Material: luminaire in anodized anticorodal turned aluminium / Anti-glare shield and stem in anodized anticorodal extruded aluminium / Die-cast aluminium base

Diffuser: ultra-white transparent tempered glass

External 24V DC driver for parallel connection, compliant with EN 61347-2-13 Standard, to be ordered separately

PWM dimmable with dedicated external driver, compliant with EN 61347-2-13 Standard, to be ordered separately

Light source: LED unit

Supplied with 1,5 m cable (from the luminaire)

Finish: anodization

On request versions (additional code):
MT7 7 m cable length

Dimensions	Ø 70 x L 180 x H 900 mm
Light source	LED
Wattage	4 W
Power supply	24 Vdc
Light source output	470 lm
System output	355 lm
System efficiency	89 lm/W
Color Rendering Index – CRI	80
LED energy class	E (3000K), E (4000K), F (2700K)
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class III
IP rating	IP 65/67
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

OS NATURAL ANODIZATION
ON BLACK ANODIZATION

COLOUR TEMP.


27K 2700K
3K 3000K
4K 4000K

OPTIC

standard 30°
optional optics
10 10°
54 54°


ACCESSORIES

ACCESSORIES
SPIKE




4696

ACCESSORIES
ANCHOR PLATE



4697

ACCESSORIES
IN-GROUND BOX



4698

ACCESSORIES
24V DRIVER – 24W



1924

ACCESSORIES
24V DRIVER – 60W



1925

ACCESSORIES
PWM DRIVER



1953