



Outdoor luminaire for wall installation

Material: extruded aluminium body / Frames with flush diffuser / Wall support in low copper content die-cast aluminium

Diffuser: milled and tempered transparent glass, flush with the structure

Built-in driver

Light source: LED unit

Rear cable entry

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

**D** Dimmable version

Dimensions	Ø 120 x H 270 x 176 mm
Light source	LED
Multiple sources	2x
Wattage	38 W
Power supply	220-240 V   50/60 Hz
Light source output	5522 lm
System output	4700 lm
System efficiency	124 lm/W
Color Rendering Index – CRI	80
LED energy class	E
LED lifetime	L80 B10 86.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 08 (5 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

### CODE OPTIONS

#### FINISH

**AG** ALUMINIUM GREY  
**AN** ANTHRACITE  
**BI** WHITE

on request:

**CO** CORTEN  
**BR** BRONZE

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K

#### OPTIC

**standard** 35°

optional optics

**15** 15°  
**90** 90°