



Outdoor luminaire for wall/ceiling installation
 Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate
 Diffuser: moulded opal glass / Silicone sealing gasket
 Built-in driver
 Light source: LED unit
 Cable entry from either the rear or the side
 Stainless steel Allen screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

| | |
|--|---------------------------------|
| Dimensions | Ø 198 x 120 mm |
| Light source | LED |
| Wattage | 8 W |
| Power supply | 220-240 V 50/60 Hz |
| Light source output | 1245 lm |
| System output | 498 lm |
| System efficiency | 62 lm/W |
| Color Rendering Index – CRI | 80 |
| LED energy class | D (3000K), D (4000K), E (2700K) |
| LED lifetime | L80 B20 > 80.000 h |
| Standard Deviation Color Matching (SDCM) | MacAdam step 3 |
| Electrical insulation class | Class I |
| IP rating | IP 65 |
| Impact resistance rating | IK 08 (5 Joules) |
| Norms | EN 60598-1 +2-1 |
| Conformity | CE UK CA |

CODE OPTIONS

FINISH

AG ALUMINIUM GREY
AN ANTHRACITE
BI WHITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

KASKO THE SERIES

