



Outdoor luminaire for wall/ceiling installation

Material: housing and base in low copper content die-cast aluminium / Aluminium internal plate

Diffuser: UV resistant opal polycarbonate / Silicone sealing gasket

Built-in driver

Light source: LED unit

Cable entry from either the rear or the side

Stainless steel Allen screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):
D Dimmable version

Dimensions	Ø 198 x 134 mm
Light source	LED
Wattage	8 W
Power supply	220-240 V 50/60 Hz
Light source output	1245 lm
System output	249 lm
System efficiency	31 lm/W
Color Rendering Index – CRI	80
LED energy class	D (3000K), D (4000K), E (2700K)
LED lifetime	L80 B20 > 80.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 65
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH		COLOUR TEMP.	
AG	ALUMINIUM GREY	27K	2700K
AN	ANTHRACITE	3K	3000K
BI	WHITE	4K	4000K

KASKO Ø 198 with eyelid - vandalproof LED 8W VANDALPROOF 9179



KASKO THE SERIES

