



Outdoor luminaire for wall installation
 Material: low copper content die-cast aluminium
 Photo-etched polycarbonate diffuser to grant a homogeneous effect with diffused light
 Built-in driver
 Light source: LED unit
 Rear cable entry
 Stainless steel screws
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	217 x 106 x 46 mm
Light source	LED
Wattage	9 W
Power supply	100-240 V 50/60 Hz
Light source output	1077 lm
System output	745 lm
System efficiency	83 lm/W
Color Rendering Index – CRI	80
LED energy class	F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 07 (2 Joules)
Norms	EN 60598-1 +2-1
Weight	0.98 kg
Conformity	CE UK CA

CODE OPTIONS

FINISH	COLOUR TEMP.	OPTIC
AG ALUMINIUM GREY	27K 2700K	
AN ANTHRACITE	3K 3000K	
CO CORTEN	4K 4000K	
BR BRONZE		
BI WHITE		