

Pole complete with luminaire

Material: extruded aluminium / Die-cast aluminium pole-top / Stainless steel base

Photo-etched polycarbonate diffuser to grant a homogeneous effect with diffused light

Built-in driver

Light source: LED unit

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	217 x 46 x H 300 mm
Light source	LED
Wattage	9 W
Power supply	100-240 V 50/60 Hz
Light source output	1077 lm
System output	745 lm
System efficiency	83 lm/W
Color Rendering Index – CRI	80
LED energy class	D (4000K), F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 07 (2 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

- AN** ANTHRACITE
- CO** CORTEN
- BR** BRONZE

COLOUR TEMP.

- 27K** 2700K
- 3K** 3000K
- 4K** 4000K


OPTIC

- standard** DIFFUSE



ACCESSORIES

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR




1944

ACCESSORIES
WATERPROOF CONNECTOR



1942

VOID POST
ANCHOR PLATE



1358