



Pole complete with luminaire

Material: extruded aluminium / Die-cast aluminium pole-top / Stainless steel base

Photo-etched polycarbonate diffuser to grant a homogeneous effect with diffused light

Built-in driver

Light source: LED unit

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	217 x 46 x H 300 mm
Light source	LED
Wattage	9 W
Power supply	100-240 V 50/60 Hz
Light source output	1077 lm
System output	745 lm
System efficiency	83 lm/W
Color Rendering Index – CRI	80
LED energy class	D (4000K), F
LED lifetime	L70 B50 > 50.000 h
Standard Deviation Color Matching (SDCM)	MacAdam step 3
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 07 (2 Joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE
CO CORTEN
BR BRONZE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K

OPTIC

standard DIFFUSE



ACCESSORIES

ACCESSORIES
WATERPROOF CONNECTOR



1941

ACCESSORIES
WATERPROOF CONNECTOR



1944

ACCESSORIES
WATERPROOF CONNECTOR



1942

VOID POST
ANCHOR PLATE



1358