

Pole complete with luminaire

Material: extruded aluminium / Die-cast aluminium pole-top / Stainless steel base

Photo-etched polycarbonate diffuser to grant a homogeneous effect with diffused light

Built-in driver

Light source: LED unit

Supplied with H05RN-F pre-wired cable (optional waterproof connections to be ordered separately)

Stainless steel screws

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

- D Dimmable version
- LV 24÷48V low voltage

Dimensions	<b>217 x 46 x H 600 mm</b>
Light source	<b>LED</b>
Wattage	<b>9 W</b>
Power supply	<b>100-240 V   50/60 Hz</b>
Light source output	<b>1077 lm</b>
System output	<b>745 lm</b>
System efficiency	<b>83 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>F</b>
LED lifetime	<b>L70 B50 &gt; 50.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 07 (2 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Weight	<b>3.1 kg</b>
Conformity	<b>CE UK CA</b>

### CODE OPTIONS

#### FINISH

**AN** ANTHRACITE  
**CO** CORTEN  
**BR** BRONZE

#### COLOUR TEMP.

**27K** 2700K  
**3K** 3000K  
**4K** 4000K


#### OPTIC

**standard** DIFFUSE



ACCESSORIES

ACCESSORIES  
WATERPROOF CONNECTOR



1941

ACCESSORIES  
WATERPROOF CONNECTOR




1944

ACCESSORIES  
WATERPROOF CONNECTOR



1942

VOID POST  
ANCHOR PLATE



1358