



Outdoor luminaire for pole installation

It can be installed on Goccia Illuminazione Ø 76 mm dedicated steel poles or on standard Ø 60 mm metal poles

Material: low copper content die-cast aluminium

Diffuser: ultra-white transparent tempered glass with black screen printing for maximum visual comfort, sealed to the frame for maximum tightness

Built-in driver

Light source: highly performing LED modules / Symmetric and asymmetric STRADA optics

Easier wiring to the inspection door thanks to the 3x1,5 cable, 4 m long; further M16 cable gland for additional wiring

Optional surge protection device (SPD) to be ordered separately

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

D6 Virtual midnight

Dimensions	<b>Ø 360 x H 198 mm</b>
Light source	<b>LED</b>
Wattage	<b>35 W</b>
Power supply	<b>220-240 V   50/60 Hz</b>
Light source output	<b>4212 lm</b>
System output	<b>2749 lm</b>
System efficiency	<b>79 lm/W</b>
Color Rendering Index – CRI	<b>80</b>
LED energy class	<b>D</b>
LED lifetime	<b>L90 B10 &gt; 100.000 h</b>
Standard Deviation Color Matching (SDCM)	<b>MacAdam step 3</b>
Electrical insulation class	<b>Class I</b>
IP rating	<b>IP 66</b>
Impact resistance rating	<b>IK 08 (5 Joules)</b>
Norms	<b>EN 60598-1 +2-1</b>
Conformity	<b>CE UK CA</b>

**CODE OPTIONS**

**FINISH**

**AN** ANTHRACITE

on request:

**AG** ALUMINIUM GREY

**COLOUR TEMP.**

**27K** 2700K

**3K** 3000K

**4K** 4000K

**OPTIC**

**standard** 100°

optional optics

**02** 150° X 45°

**03** 90° X 30°

**04** 120° X 45°

**05** 150° X 70°



ACCESSORIES

ACCESSORIES  
SPD



1965

ACCESSORIES  
POLE H 2500 – BURIABLE



3504

ACCESSORIES  
POLE H 3000 – BURIABLE



3505

ACCESSORIES  
POLE H 3500 – BURIABLE



3506