



Pole complete with luminaire

Material: extruded aluminium / Luminaire and internal fixing base in low copper content die-cast aluminium

Diffuser: clear polycarbonate

Built-in driver

Light source: circle ring LED module

Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer

Stainless steel screws

Optional surge protection device (SPD) to be ordered separately

Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 120 x H 1180 mm
Light source	LED
Wattage	20 W
Power supply	220-240 V   50/60 Hz
System output	2727 lm
System efficiency	136 lm/W
Color Rendering Index – CRI	80
LED energy class	B (4000K), C (2700K), C (3000K)
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

## CODE OPTIONS

### FINISH

<b>AG</b>	ALUMINIUM GREY
<b>AN</b>	ANTHRACITE
<b>CO</b>	CORTEN
<b>BR</b>	BRONZE


### COLOUR TEMP.

<b>27K</b>	2700K
<b>3K</b>	3000K
<b>4K</b>	4000K



ACCESSORIES

ACCESSORIES  
ANCHOR PLATE



5538

ACCESSORIES  
SPD



1965