



Urban lighting pole complete with luminaire  
 Equipped with buriable anchoring unit  
 Anti-glare collar built into the lamp body  
 Material: extruded aluminium / Luminaire in low copper content die-cast aluminium  
 Diffuser: clear polycarbonate  
 Built-in driver  
 Light source: circle ring LED module  
 Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer  
 Stainless steel screws  
 Optional surge protection device (SPD) to be ordered separately  
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 120 x H 2680 mm
Light source	LED
Wattage	29 W
Power supply	220-240 V   50/60 Hz
Color Rendering Index – CRI	80
LED energy class	B (4000K), C (2700K), C (3000K)
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

**CODE OPTIONS**

FINISH		COLOUR TEMP.	
<b>AN</b>	ANTHRACITE	<b>27K</b>	2700K
		<b>3K</b>	3000K
		<b>4K</b>	4000K



ACCESSORIES

