



Urban lighting pole complete with luminaire
 Equipped with buriable anchoring unit
 Anti-glare collar built into the lamp body
 Material: extruded aluminium / Luminaire in low copper content die-cast aluminium
 Diffuser: clear polycarbonate
 Built-in driver
 Light source: circle ring LED module
 Watertight wiring through the supplied cable that powers the integrated driver. Further M16 cable gland for additional wiring, positioned in the lower part of the closing cap in technopolymer
 Stainless steel screws
 Optional surge protection device (SPD) to be ordered separately
 Finish with double painting (epoxy-based primer and polyester powder coating) after anti-corrosion treatments

On request versions (additional code):

D Dimmable version

Dimensions	Ø 120 x H 2680 mm
Light source	LED
Wattage	29 W
Power supply	220-240 V 50/60 Hz
Color Rendering Index – CRI	80
LED energy class	B (4000K), C (2700K), C (3000K)
Electrical insulation class	Class I
IP rating	IP 66
Impact resistance rating	IK 10 (20 joules)
Norms	EN 60598-1 +2-1
Conformity	CE UK CA

CODE OPTIONS

FINISH

AN ANTHRACITE

COLOUR TEMP.

27K 2700K
3K 3000K
4K 4000K



ACCESSORIES

